

Safety cabinets – Combi-Line

-  FIRE RESISTANCE GRADE LFS 30 P
Certified protection against fire
-  RESISTANCE GRADE S2
Certified protection against burglary
-  VdS
Currently the only certified safe lock with
fingerscan module



Version E:
optionally available with
fingerscan module












CL 10 - CL 40 Safety cabinets 'Combi-Line'

**SECURITY LEVEL S 2
FIRE RESISTANCE GRADE LFS 30 P**

- BURG-WÄCHTER safety cabinets with a certification which is valid all over Europe. For the safe storage of documents, cash, jewellery, arms or ammunition, coins and valuables.
- security Level S 2 according to DIN EN 14450
- security Level B according to VDMA 24992, May 1995
- fire resistance LFS 30 P according to EN 15659 – 30 minutes fire protection for paper
- fire-protective material according to DIN 4102
- composite insulation in front of the door leaf provides heat protection for the lock and bolts
- tested and certified protection against burglary and fire
- double-walled construction
- internal hinge
- lateral locking through 25mm diameter strong round bolts plus sliding bolt on the top
- all-over gripping rail on the hinge side
- prepared for both wall and floor fixing, fixings included - extreme high breaking strength, 2 diagonally arranged drill holes on the back wall and 2 on the bottom
- colour: body grey, door light grey
- model S supplied with 2 keys
- standard series with 1 shelf each



SecuTronic – the first biometric safe lock with VdS certification. Developed by BURG-WÄCHTER.

- certified safe lock with integrated fingerscan module according to VdS, EN 1300 class 1
- programmable electronic combination lock 'SecuTronic' with integrated fingerscan module
- in addition to a 6-digit user programmed code, up to 10 fingers can be programmed
- 1.000.000 different combinations possible
- when opening with fingerscan, 2 different fingers have to be programmed/entered
- the scanner only works with 'real, live, fingers'. Fake fingers or copies will not be identified
- the precise and highly sensitive procedure of authentication operates with different dermal conditions, from extremely dry up to humid skin
- the opening of a safe by using the fingerscan is very quick and comfortable

VdS TESTED Currently the only certified safe lock with fingerscan module



3 security standards in one safe.

The safety cabinets Combi-Line correspond to 3 security standards:

- level B according to VDMA24992, 5/95
- level S 2 according to DIN EN 14450
- fire resistance LFS 30 P according to EN 15659 - 30 minutes fire protection for paper

Technical features.

Sliding bolt on the top with additional protection against attack.



Safety cabinets – Combi-Line



Version S

Security safe lock 'SecuSafe', VdS tested, ECB-S certified according to EN 1300 class A, 9 levers, more than 1.000.000 key differs.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
CL 10 S	33400 3	320 x 435 x 380	205 x 320 x 232	205 x 265	44	15
CL 20 S	33420 1	360 x 495 x 445	245 x 380 x 297	245 x 325	55	27
CL 40 S	33440 9	560 x 495 x 445	445 x 380 x 297	445 x 325	77	50

Key blank for CL 10-40 S

Key	EAN	
	40 03482...	
As per sample	16620 8	Length of key 80 mm
Key blank 55	33610 6	Key blank, PU 3 pcs.



CL 10 S



Version E

Electronic combination lock 'SecuTronic', VdS tested, ECB-S certified according to EN 1300 class B, 1.000.000 different combinations possible, incl. 3 batteries, type Micro LR 03 AAA. The locking armature protrudes 7 mm.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
CL 10 E	33410 2	320 x 435 x 380	205 x 320 x 232	205 x 265	44	15
CL 20 E	33430 0	360 x 495 x 445	245 x 380 x 297	245 x 325	55	27
CL 40 E	33450 8	560 x 495 x 445	445 x 380 x 297	445 x 325	77	50



CL 20 S



Version E FS

Programmable electronic lock 'SecuTronic' with integrated fingerscan module, VdS certified according to EN 1300 class 1, 1,000,000 different combinations possible. Includes batteries, including batteries, in addition to a 6-digit user-programmed numerical code up to 10 fingers can be programmed, for opening with a fingerscan two fingers must be programmed/entered. The locking armature protrudes 13 mm.



Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
CL 10 E FS	33460 7	320 x 435 x 380	205 x 320 x 232	205 x 265	44	15
CL 20 E FS	33470 6	360 x 495 x 445	245 x 380 x 297	245 x 325	55	27
CL 40 E FS	33480 5	560 x 495 x 445	445 x 380 x 297	445 x 325	77	50



CL 20 E



Appropriate for storage of weapons or ammunition


Optimal utilisation of the interior space



CL 10



CL 20



CL 40



CL 40 E FS

BURG-WÄCHTER Security-Level

	LEVEL	0	10	20
	LEVEL	0	10	20
	LEVEL	0	5	10
	LEVEL	0	7	10
	LEVEL	0	8	10

ISO 9001 CERTIFIED
BURG-WÄCHTER
MEMBER OF VdS

GERMAN ENGINEERING
QUALITY